

AMENDMENT TO THE CLAIMS

Please cancel claim 8.

Please amend claims 1-7, 9-12, 15-17, and 25 as shown below.

1. (Currently Amended) A system for introducing payloads into earth orbit, comprising:

a reusable orbital vehicle capable of being placed in earth orbit, the orbital vehicle having an outer skin ~~surface formed by;~~

a thermal protection system attached to the outer skin of the orbital vehicle to thereby form an outermost layer of the orbital vehicle, the thermal protection system being formed by materials capable of withstanding environmental temperatures associated with re-entry of the orbital vehicle to thereby maintain operational viability of the orbital vehicle during re-entry;

~~a plurality of attachment positions located on the outer skin surface of the orbital vehicle~~ an internal payload coupled to an interior portion of the orbital vehicle;
and

a first ~~experimental-external payload~~ package affixed to the orbital vehicle at a first ~~one of the plurality of attachment positions~~ position on the outermost layer of the orbital vehicle wherein the first ~~experimental-external payload~~ package is exposed to the external atmosphere during launch and re-entry phases of a space mission and is further exposed to the environment of space while in orbit wherein the first attachment position is located such that destruction of the first external payload package will not affect the operational viability of the orbital vehicle.

2. (Currently Amended) The system of claim 1, further comprising a second ~~experimental-external payload~~ package affixed to the orbital vehicle at a second ~~one of the plurality of attachment positions~~ position on the outermost layer of the orbital vehicle wherein the second ~~experimental-external payload~~ package is exposed to the external atmosphere during launch and re-entry phases of the space mission and is further exposed to the environment of space while in orbit.

3. (Currently Amended) The system of claim 2 wherein the first and second ~~experimental-external payload packages~~ have uniform predetermined dimensions, the first and second ~~ones of the plurality of~~ attachment positions being configured to receive and retain the first and second ~~experimental-external payload packages~~ at the first and second ~~ones of the plurality of~~ attachment positions.

4. (Currently Amended) The system of claim 1, ~~wherein the first experimental package comprises a thermal protection system further a carrier plate assembly positioned at the first attachment position to receive and retain the first external payload package.~~

5. (Currently Amended) The system of claim 1, further comprising an access panel on ~~the outer skin surface of the reusable orbital vehicle~~ wherein ~~at least one of the plurality of first attachment positions~~ position is located on the access panel.

6. (Currently Amended) The system of claim 5 wherein the access panel on ~~the outer skin surface of the reusable orbital vehicle~~ is removable from the ~~reusable orbital vehicle~~.

7. (Currently Amended) The system of claim 1, further comprising a carrier plate configured for attachment at the first ~~one of the plurality of attachment positions~~ position and further configured for attachment to the first ~~experimental-external payload package~~ wherein the carrier plate is intermediate the outer skin surface of the orbital vehicle and the first ~~experimental~~ package.

8. (Canceled)

9. (Currently Amended) The system of claim 1 wherein the orbital vehicle has an elongated shape with first and second ends with a rocket engine positioned proximate the second end of the orbital vehicle, the first ~~of the plurality of attachment positions~~ position being on the ~~exterior skin~~ outermost layer of the orbital vehicle substantially at the first end.

10. (Currently Amended) The system of claim 1 wherein the orbital vehicle has an elongated shape with first and second ends with a rocket engine positioned proximate the second end of the orbital vehicle, the first ~~of the plurality of attachment positions~~ position being on the ~~exterior skin outermost layer~~ of the orbital vehicle forward of a midpoint between the first end and the second end.

11. (Currently Amended) The system of claim 1 wherein the orbital vehicle has an elongated shape with first and second ends with a rocket engine positioned proximate the second end of the orbital vehicle, the first ~~of the plurality of attachment positions~~ position being on the ~~exterior skin outermost layer~~ of the orbital vehicle rearward of a midpoint between the first end and the second end.

12. (Currently Amended) The system of claim 1 wherein the orbital vehicle has an elongated shape with first and second ends with a rocket engine positioned proximate the second end of the orbital vehicle, the system further comprising an aft skirt proximate the second end wherein the first ~~of the plurality of attachment positions~~ position is on an exterior skin portion of the aft skirt.

13. (Original) The system of claim 1 wherein the orbital vehicle has an elongated shape with first and second ends with a rocket engine positioned proximate the second end of the orbital vehicle, the system further comprising an aft skirt proximate the second end and a protected attachment position on an interior portion of the aft skirt.

14. (Original) The system of claim 1 wherein the orbital vehicle has an elongated shape with first and second ends with a rocket engine positioned proximate the second end of the orbital vehicle, the system further comprising an aft skirt proximate the second end and an attachment member mounted to an interior portion of the aft skirt.

15. (Currently Amended) ~~The system of claim 14 wherein the~~A system for introducing payloads into earth orbit, comprising:

a reusable orbital vehicle capable of being placed in earth orbit, the orbital vehicle having an elongated shape with first and second ends with a rocket engine positioned proximate the orbital vehicle second end;

an aft skirt proximate the orbital vehicle second end, and

an attachment member is-rotatably mounted to the~~an~~ interior portion of the aft skirt.

16. (Currently Amended) The system of claim—~~14~~15, further comprising a mounting bracket fixedly mounted to the interior portion of the aft skirt wherein the attachment member is moveably coupled to the mounting bracket.

17. (Currently Amended) The system of claim 16, further comprising a control system to control movement of the attachment member to move the attachment member and thereby position ~~a second experimental~~an external payload package outside the interior portion of the aft skirt.

18. (Original) The system of claim 14 wherein the attachment member comprises a base portion having first and second ends, the base portion first end being coupled to the interior portion of the aft skirt, an intermediate portion having first and second ends, the intermediate portion first end being coupled to the coupled to the base portion second end, and a terminal portion having first and second ends, the terminal portion first end being coupled to the coupled to the intermediate portion second end.

19. (Original) The system of claim 18, further comprising a mounting bracket fixedly mounted to the interior portion of the aft skirt wherein the base portion first end is rotatably coupled to the mounting bracket.

20. (Original) The system of claim 18 wherein the terminal portion first end is rotatably coupled to the intermediate portion second end.

21. (Original) The system of claim 18, further comprising a mounting member coupled to the terminal portion second end and configured to receive the second experimental package.

22. (Original) The system of claim 1, further comprising a sensor associated with the first experimental package, the sensor generating sensor data.

23. (Original) The system of claim 22, further comprising a data storage unit electrically coupled to the orbital vehicle and electrically coupled to the sensor, the data storage unit receiving and storing the generated sensor data.

24. (Original) The system of claim 23 for use with an avionics data bus on the orbital vehicle to monitor operation of the orbital vehicle, the data storage unit being coupled to the avionics data bus on the orbital vehicle to store data related to the operation of the orbital vehicle in association with the generated sensor data.

25. (Currently Amended) The system of claim 22 wherein the first ~~experimental-external payload~~ package comprises a thermal protection system.

26. (Original) The system of claim 1, further comprising an initial stage coupled to the orbital vehicle to boost the orbital vehicle from a position on earth to a predetermined altitude.

27. (Original) A system for introducing payloads into earth orbit, comprising:

a reusable orbital vehicle capable of being placed in earth orbit, the orbital vehicle an elongated body portion with first and second ends with a rocket engine positioned proximate the second end of the orbital vehicle;

an aft skirt coupled to the body portion proximate the second end and extending circumferentially around the rocket engine; and

an attachment member mounted to an interior portion of the aft skirt, the attachment member configured to receive an experiment.

28. (Original) The system of claim 27 wherein the attachment member is rotatably mounted to the interior portion of the aft skirt.

29. (Original) The system of claim 27 wherein the attachment member is moveably mounted to the interior portion of the aft skirt, the system further comprising a control system to control movement of the attachment member to move the attachment member and thereby position the experiment outside the interior portion of the aft skirt.

30. (Original) The system of claim 29 wherein the experiment is an experimental control surface.

31. (Original) The system of claim 30 wherein the control system provides steering control of the attachment member to thereby steer the experiment while positioned outside the interior portion of the aft skirt.

32. (Original) The system of claim 27 wherein the attachment member comprises a base portion having first and second ends, the base portion first end being coupled to the interior portion of the aft skirt, an intermediate portion having first and second ends, the intermediate portion first end being coupled to the coupled to the base portion second end, and a terminal portion having first and second ends, the terminal portion first end being coupled to the coupled to the intermediate portion second end.

33. (Original) The system of claim 32, further comprising a mounting bracket fixedly mounted to the interior portion of the aft skirt wherein the base portion first end is moveably coupled to the mounting bracket.

34. (Original) The system of claim 32 wherein the terminal portion first end is moveably coupled to the intermediate portion second end.

35. (Original) The system of claim 32, further comprising a mounting member coupled to the terminal portion second end and configured to receive the experiment.

36. (Original) The system of claim 27, further comprising a sensor associated with the experiment, the sensor generating sensor data and a data storage unit to receive and store the generated sensor data.

37-70 (Canceled)